



VG- 515 Full HD PTZ Camera



Full HD, Wide View Angle, Multiple Zoom Lens, Multiple Video Interfaces and Multiple protocols

This camera offers perfect functions, superior performance and rich interfaces. The features include advanced ISP processing algorithms to provide vivid images with a strong sense of depth, high resolution, and fantastic color rendition.

Specification

| | |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor | 1/2.9 Inch High Quality CMOS Sensor |
| Effective Pixels | 2.07MP, 16:9 |
| Video Format | 1920×1080P@30 fps/25fps; 1280×720P@30fps/25fps; 1024×576P@30fps/25fps; 960×540P@30fps/25fps; 800×448P@30fps/25fps; 640×360P@30fps/25fps; 320×176P@30fps/25fps |
| Optical Lens | f=4.34mm~41.66mm |
| View Angle | 8.8°~70° |
| Iris | F1.85 – F2.43 |
| Optical Zoom | 10x |
| Digital Zoom | 10X |
| Low Illumination | 0.5Lux(F1.8, AGC ON) |
| DNR | 2D & 3D DNR |
| White Balance | Auto / Manual/ One Push//3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K |
| Focus | Auto / Manual/ One Push/ |
| Exposure | Auto / Manual |
| BLC | On/Off |
| WDR | OFF/ Dynamic Level Adjustment |



| | |
|---------------------------------|---------------------------------------------------------------------------|
| Video Adjustment | Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve |
| SNR | >50dB |
| Interface and Protocol | |
| Video Output | USB2.0 (Type A) |
| Control Port | RS232(Circuit), RS485 |
| Control Protocol | Protocol: VISCA/Pelco-D/Pelco-P |
| Power Supply | HEC3800 Outlet (DC12V) |
| USB characteristics | |
| Support operating system | Windows 7,Windows8,Windows10,Mac, Linux |
| Video Compression | H.265, H.264, MJPG |
| communication protocol | UVC |
| PTZ Parameter | |
| Pan/Tilt Rotation | -170°~+170°, -30°~+30° |
| Pan/Tilt Control Speed | 0.~60°/Sec, 0.~30°/Sec |
| Preset Speed | Pan:60°/Sec, Tilt: 30°/Sec |
| Preset Numbers | 255 Points Preset (10 points By Remote Controller) |
| Other Parameter | |
| Working Voltage | 12V |
| Working current | 0.25A(max) |
| Power Consumption | 2.5W(max) |
| Storage Temperature | -10°C~+60°C, 20%~95% |
| Working Temperature | -10°C~+50°C, 20%~80% |
| Dimension | 156.8mm×112.6mm×139.5mm |
| Weight | About 1kg |
| Usage | Indoor Only |
| Package | Power supply, Remote Controller, Manual, Warranty Card, USB2.0 Cable |
| Accessories Optional | Mount (Extra Cost) |